

Chipboard



Chipboard P2

P2 chipboard is for **dry use only**.

Straight edge

	Thickness in mm										
Size in mm	8	10	13	15	16	18	19	22	25	28	38
2800 x 2070	30	30	30	30	30	26	26	20	20	10	10
4100 x 2070	30	30	30		20		20	20	10	10	10
3300 x 2070					20		20				

Chipboard P3

P3 chipboard is for **damp/high humidity use and for NON-supporting purposes**.

Straight edge

	Thickness in mm			
Size in mm	13	16	19	25
2827 x 2064			28	
4100 x 2070	30	20	20	10

4-side tongue and groove

	Thickness in mm							
Size in mm	10	13	16	19	22	25	28	38
2050 x 925	70	54	44	37	32	28	25	18

Chipboard P5


P5 chipboard is for **supporting purposes in the area of damp/high humidity use**.


Straight edge

	Thickness in mm				
Size in mm	12	16	19	22	25
2827 x 2064	40	34	28	26	22

4-side tongue and groove

	Thickness in mm	
Size in mm	19	22
2050 x 925	37	32

 xx Number of beams per package

 Express programme – available at short notice

 available to order

Further product information, such as technical datasheets, are available for download at www.bischoff-schaefer.de

**BISCHOFF
+
SCHÄFER**